










Embases acier massif

Ø 50

Embase acier
Tige acier
Pied articulé oscillant

Version inox p. 122



CODE		DÉSIGNATION	DIMENSIONS								CHARGE MAXI
Standard	avec semelle		A	B	D		M	G	H	H1	Newton
MA-15400	MA-15400/G	M10x50	19	50	50	14 	M10	11,5	69	72	15 000
MA-15401	MA-15401/G	M10x100	19	100	50	14 	M10	11,5	119	122	15 000
MA-15402	MA-15402/G	M12x50	19	50	50	14 	M12	11,5	69	72	15 000
MA-15403	MA-15403/G	M12x100	19	100	50	14 	M12	11,5	119	122	15 000
MA-15404	MA-15404/G	M12x125	19	125	50	14 	M12	11,5	144	147	15 000
MA-15402/14	MA-15402/14/G	M14x50	19	50	50	14 	M14	11,5	69	72	15 000
MA-15403/14	MA-15403/14/G	M14x100	19	100	50	14 	M14	11,5	119	122	15 000
MA-15404/14	MA-15404/14/G	M14x125	19	125	50	14 	M14	11,5	144	147	15 000

matière

Embase en acier zingué C40.
Tige en acier zingué livrée sans écrou. Semelle en caoutchouc
NBR dureté 70° shore H6 (80° sur demande).

note

Réalisation de dimensions et finitions spéciales de tiges filetées dès 200 pièces.

